Product Name: Product Description: Product Code:

Adventure Wear Expedition Lo High performance outdoor styling RE425BR (Brown) or RE425BK (Black)

AFRICA'S HARDEST WORKING BOOTS







Materials

CE EN ISO 20345 : 2011 - S3



Upper	High quality Nu-Buck Leather Upper	
Inner Sole	Padded Anti-microbial Foam with	
	Anti-Static Properties	
Lining	Breathable and Abrasion Resistant lining	

Toe Cap Eyelet Sole

EN-Approved Carbon Steel Fabric Loops and Polyurethane Rings **EVA Rubber**

Specifications

Specifications	
Specifications	 European Norm EN 20345 :2011 - S3 SABS APPROVED Tested by ITS - an internationally recognized testing facility
Special Features	 Padded Inner Sole allows greater comfort Steel Mid Sole for anti-penetration Upper has S2 Water-resistant property Sole offers exceptional gripping qualities EVA Rubber sole designed to ensure high durability Padded Bellows Tongue ensure additional comfort Padded Upper Collar ensures increased comfort Rubber Toe-Bumper for added scuff protection
Sole	 Temperature Maximum 120°C (degrees Celsius) Oil and acid resistant EVA/Rubber Slip Resistance - Tested to EN345 and meets these requirements However, care should always be taken on wet or oily surfaces Crack Resistance - Tested to 30,000 flex cycles
Тое Сар	Steel Toe Cap - Tested to an impact resistance of 200 Joules
Anti Static Properties Sizing Lifespan	 Product is anti static. If application is life critical additional consultation with product expert is required. Electrical resistance can be significantly changed by flexing, contamination or moisture. Introduction of additional inner sole reduces static resistance Available from Size 4 to Size 13 (Unisex) The application determines the length of service that should be achieved. Normal environments should provide 12 months' service, if appropriate care is taken. Refer Care guidelines

Uses **Suitability** Comments

General Construction	Highly suitable Highly suitable	
Mining	Widely used	
Petrochemical	Widely used	
Engineering	Highly suitable	
Power Generation	Widely used	
Agriculture	Highly suitable	
Food & Health	Not recommended	
Fishing & Allied Industries	Widely used	
Fabrication	Highly suitable	
Metal Industries	Widely used	Temperature limitations must be observed
Motor Industry	Widely used	
Glass Manufacturing & Fabrication	Widely used	Steel midsole advised to protect against glass penetration of the sole (Ref: RE608, RE210-S3, FX2-S1P,
Municipality	Widely used	RE424, RE425)
Waste Disposal	Widely used	Steel midsole advised to protect against penetration of the sole (Ref: RE608, RE210-S3, FX2-S1P,
Civil Contracting	Highly suitable	RE424, RE425)
Moving and Rigging	Highly suitable	
Forestry	Highly suitable	
Telecommunications	Highly suitable	In the appropriate job requirement
Contract Labour	Widely used	
Transport - Air, Road & Rail	Widely used	
Transport - Shipping	Widely used	

It is important that the footwear selected must be suitable for the protection required by the wearer and the environment. If any uncertainty exists consultation between buyer and seller should be conducted to ensure that the correct footwear is selected. This application guide only offers very general advice and should be confirmed if there may be any concerns over potential protection from hazards of any form.

To view the complete REBEL Safetygear range, please visit: www.rebelsafetygear.com