AFRICA'S HARDEST WORKING BOOTS

Product Name:

Product Code:









Materials		CE EN IS	SO 20345 : 2011 - S1	
Classic on ind	High Quality, Full Grain Cow Buffalo Leather Classic styled, formal shoe offering no compromises on industrial safety features Biagioli IBITECH 252 2mm Foam Insole Board		Breathable and Abrasion Resistant Tai-brella (Equivalent to Cambrelle) Steel Toe Cap Lightweight and comfortable Dual Density Poly Urethane Sole	
Specifications				
Specifications	Specifications• European Norm EN ISO 20345 :2011 - S1 • Tested by SATRA - Approved Body Identification Number : 0321			
Sole	 Temperature Maximum 90°C (degrees Celsius) Oil and acid resistant Dual Density PU Slip Resistance - Tested to SATRA PM144 1992 and meets these requirements However, care should always be taken on wet or oily surfaces Crack Resistance - Tested to 30,000 flex cycles 			
Тое Сар	• Steel toe cap - Tested to an impact re	sistance of 20	00 Joules	
Anti Static Properti	 Product is anti static. If application is life critical additional consultation with product expert is required. Electrical resistance can be significantly changed by flexing, contamination or moisture. Introduction of additional inner sole reduces static resistance 			
Sizing	• Available from Size 4 to Size 13			
Lifespan	• The application determines the length of service that should be achieved. Normal environments should provide 12 months' service, if appropriate care is taken. Refer Care guidelines			

Uses	Suitability	Comments
Uniform Footwear	Highly suitable	
General	Highly suitable	Suitable as a go between the office and the workshop
Construction	Not suitable	
Mining	Not suitable	
Petrochemical	Not suitable	
Engineering	Not suitable	
Power Generation	Not suitable	
Agriculture	Suitable	
Food & Health	Widely used	Reference to chemical resistance in cleaning areas may be necessary
Fishing & Allied Industries	Not suitable	
Fabrication	Not suitable	
Metal Industries	Not suitable	Temperature limitations must be observed
Motor Industry	Suitable	
Glass Manufacturing and Fabrication	Not suitable	Steel midsole advised to protect against glass penetration of the sole - (Ref: RE608-S3, FX2-S1P, RE210-S3,
Municipality	Suitable	RE424, RE425)
Waste Disposal	Not suitable	Steel midsole advised to protect against penetration of the sole - (Ref: RE608-S3, FX2-S1P, RE210-S3, RE424
Civil Contracting	Not suitable	RE425)
Moving and Rigging	Not suitable	
Forestry	Not suitable	
Telecommunications	Widely used	
Contract Labour	Not suitable	
Transport - Air, Road & Rail	Not suitable	
Transport - Shipping	Not suitable	

It is important that the footwear selected must be suitable for the protection required by the wearer and the environment. If any uncertainty exists consultation between buyer and seller should be conducted to ensure that the correct footwear is selected. This application guide only offers very general advice and should be confirmed if there may be any concerns over potential protection from hazards of any form.

To view the complete REBEL Safetygear range, please visit: www.rebelsafetygear.com