

Product Name: REBEL Hiker Hi
 Product Description: Hiker style safety boot
 Product Code: RE304 (Brown) or RE304BK (Black)

REBEL

SAFETY GEAR

AFRICA'S HARDEST WORKING BOOTS



REBEL
SAFETY GEAR



Materials

CE EN ISO 20345 : 2011 - S1



Upper Full Grain High Quality Waxy, smooth Leather Upper
 Inner Sole Biagioli IBITECH 252 2mm Foam Insole Board
 Lining Breathable and Abrasion Resistant Tai-brelle (Equivalent to Cambrelle)

Toe Cap Steel Toe Cap
 Eyelet Nickel-free D-Rings
 Sole Dual Density Poly Urethane REBEL Sole - injection moulded

Specifications

- | | |
|-------------------------------|---|
| Specifications | <ul style="list-style-type: none"> European Norm EN ISO 20345 :2011 -S1 SABS APPROVED Tested by SATRA - Approved Body Identification Number : 0321 |
| Special Features | <ul style="list-style-type: none"> Highly padded bellows tongue for comfort and protection from sparks & shavings High quality waxy leather upper |
| Sole | <ul style="list-style-type: none"> Temperature Maximum 90°C (degrees Celsius) Oil and acid resistant Dual Density PU Slip Resistance - Tested to SATRA PM144 1992 and meets these requirements However, care should always be taken on wet or oily surfaces Crack Resistance - Tested to 30,000 flex cycles |
| Toe Cap | <ul style="list-style-type: none"> Steel Toe Cap - Tested to an impact resistance of 200 Joules |
| Anti Static Properties | <ul style="list-style-type: none"> Product is anti static. If application is life critical additional consultation with product expert is required. Electrical resistance can be significantly changed by flexing, contamination or moisture. Introduction of additional inner sole reduces static resistance |
| Sizing | <ul style="list-style-type: none"> RE304 Brown - Available from Size 2 to Size 14 (Unisex) RE304 Black - Available from Size 3 to Size 13 (Unisex) |

Uses

Suitability

Comments

<ul style="list-style-type: none"> General Construction Mining Petrochemical Engineering Power Generation Agriculture Food & Health Fishing & Allied Industries Fabrication Metal Industries Motor Industry Glass Manufacturing & Fabrication Municipality Waste Disposal Civil Contracting Moving and Rigging Forestry Telecommunications Contract Labour Transport - Air, Road & Rail Transport - Shipping 	<ul style="list-style-type: none"> Highly suitable Widely used Widely used Widely used Highly suitable Widely used Highly suitable Widely used Widely used Highly suitable Widely used Highly suitable Widely used Highly suitable Widely used Widely used Highly suitable Widely used Widely used Highly suitable Widely used Widely used Highly suitable Widely used Widely used Widely used 	<ul style="list-style-type: none"> Care in very wet areas required. Gumboots would be more suitable for wet area applications Highly oil resistant but reference to chemical chart is recommended Reference to chemical resistance in cleaning areas may be necessary Temperature limitations must be observed Steel midsole advised to protect against glass penetration of the sole (Refer: RE608-S3, FX2-S1P, GL0830-S1P, RE424, RE425) Steel midsole advised to protect against penetration of the sole (Refer: RE608-S3, FX2-S1P, GL830-S1P, RE424, RE425) In the appropriate job requirement
--	--	---

It is important that the footwear selected must be suitable for the protection required by the wearer and the environment. If any uncertainty exists consultation between buyer and seller should be conducted to ensure that the correct footwear is selected. This application guide only offers very general advice and should be confirmed if there may be any concerns over potential protection from hazards of any form.

To view the complete REBEL Safetygear range, please visit: www.rebelsafetygear.com