

Product Name: REBEL Hiker Lo
 Product Description: Hiker style safety shoe
 Product Code: RE303 (Brown) or RE303BK (Black)

REBEL

SAFETY GEAR

AFRICA'S HARDEST WORKING BOOTS



REBEL
SAFETY GEAR



Materials

CE EN ISO 20345 : 2011 - S1



| | | | |
|------------|--|---------|---------------------------------------|
| Upper | Full Grain High Quality Waxy Smooth Leather Upper | Toe Cap | Steel Toe Cap |
| Inner Sole | Biagioli IBITECH 252 2mm Foam Insole Board | Eyelet | Nickel-free D-Rings |
| Lining | Breathable and Abrasion Resistant Tai-brelle (Equivalent to Cambrelle) | Sole | Dual Density Poly Urethane REBEL Sole |

Specifications

| | |
|------------------------|---|
| Specifications | <ul style="list-style-type: none"> European Norm EN ISO 20345 : 2011 -S1 SABS APPROVED Tested by SATRA - Approved Body Identification Number : 0321 |
| Special Features | <ul style="list-style-type: none"> Highly padded Bellows tongue for comfort and protection against sparks & shavings |
| Sole | <ul style="list-style-type: none"> Temperature Maximum 90°C (degrees Celsius) Oil and acid resistant Dual Density PU Slip Resistance - Tested to SATRA PM144 1992 and meets these requirements However, care should always be taken on wet or oily surfaces Crack Resistance - Tested to 30,000 flex cycles |
| Toe Cap | <ul style="list-style-type: none"> Tested to an impact resistance of 200 Joules |
| Anti Static Properties | <ul style="list-style-type: none"> Product is anti static. If application is life critical additional consultation with product expert is required. Electrical resistance can be significantly changed by flexing, contamination or moisture. Introduction of additional inner sole reduces static resistance |
| Sizing | <ul style="list-style-type: none"> RE303 Brown - Available from Size 2 to Size 13 (Unisex) RE303 Black - Available from Size 2 to Size 13 (Unisex) |

Uses

Suitability

Comments

| | | |
|-----------------------------------|-----------------|--|
| General | Highly suitable | |
| Construction | Widely used | |
| Mining | Widely used | Care in very wet areas required. Gumboots would be more suitable for wet area applications |
| Petrochemical | Widely used | Highly oil resistant but reference to chemical chart is recommended |
| Engineering | Highly suitable | |
| Power Generation | Widely used | |
| Agriculture | Highly suitable | |
| Food & Health | Widely used | Reference to chemical resistance in cleaning areas may be necessary |
| Fishing & Allied Industries | Widely used | |
| Fabrication | Highly suitable | |
| Metal Industries | Widely used | Temperature limitations must be observed |
| Motor Industry | Highly suitable | |
| Glass Manufacturing & Fabrication | Widely used | Steel midsole advised to protect against glass penetration of the sole (Refer to: RE608-S3, FX2-S1P, RE424, RE425) |
| Municipality | Highly suitable | |
| Waste Disposal | Widely used | Steel midsole advised to protect against penetration of the sole (Refer to: RE608-S3, FX2-S1P, RE424, RE425) |
| Civil Contracting | Widely used | |
| Moving and Rigging | Highly suitable | |
| Forestry | Widely used | |
| Telecommunications | Widely used | In the appropriate job requirement |
| Contract Labour | Highly suitable | |
| Transport - Air, Road & Rail | Widely used | |
| Transport - Shipping | Widely used | |

It is important that the footwear selected must be suitable for the protection required by the wearer and the environment. If any uncertainty exists consultation between buyer and seller should be conducted to ensure that the correct footwear is selected. This application guide only offers very general advice and should be confirmed if there may be any concerns over potential protection from hazards of any form.